

## Nokia ONT XS-2426G-A

Residential gateway ONT (XS-2426G-A)

The Nokia ONT XS-2426G-A is the solution for home networking that is delivered by 10 Gigabit symmetrical Passive Optical Network (XGS-PON). The device has built-in concurrent dual-band Wi-Fi® 802.11 b/g/n/ax and 802.11a/n/ac/ax networking with triple play capabilities that include voice, video and data. The XS-2426G-A supports Wi-Fi EasyMesh™, to create a whole home mesh network. This coverage can be expanded at any time by installing additional Wi-Fi EasyMesh-capable beacons to ensure seamless roaming throughout the home. The XS-2426G-A includes the Nokia WiFi Mesh Middleware which ensures the best possible Wi-Fi performance. The end-user experience is enhanced by the service provider's Wi-Fi management capabilities in the cloud and intuitive home user support using the Nokia WiFi mobile app.

The Nokia ONT XS-2426G-A is a dual-band Wi-Fi 6 mesh system with Wi-Fi Alliance certified Wi-Fi EasyMesh, enhanced by Nokia value added features. The Nokia WiFi Mesh Middleware creates a self-healing, self-optimizing network and includes intelligent channel selection, band steering, client steering and backhaul management to provide the best Wi-Fi performance. As it is EasyMesh™ compliant, it provides interoperability and avoids vendor lock-in.

Optionally, the Nokia ONT XS-2426G-A can be managed by the Nokia WiFi Cloud Controller. The associated Home Console presents the help desk agents with a real-time holistic view of the in-home network to assist them with easy identification and instantaneous resolution of issues. The Network Console provides an end-to-end Wi-Fi network view and allows management of groups of Wi-Fi networks.

This Nokia indoor ONT is designed to deliver triple play services (voice, video and data) to residential



subscribers. Voice services are provided through two plain old telephone service (POTS) ports with an integrated analog telephone adapter (ATA) that converts voice traffic into Session Initiation Protocol (SIP). Connectivity to an existing public switched telephone network (PSTN) Class 5 switch is supported through SIP with direct interoperability of a variety of soft switches. Ethernet connectivity is available on four Gigabit Ethernet (GigE) ports, all

of which have the ability to burst up to a full gigabit dynamically. Service providers can deliver video using IP packets (IPTV).

Relying on dual-band Wi-Fi allows for support of the widest range of customer products.

The IEEE 802.11ax standard enables gigabit speeds on many newer devices, while the widely supported 802.11b/g/n/ac standard can simultaneously connect to legacy devices.

## Features

- Four RJ-45 10/100/1000 Ethernet ports
- Two POTS ports for carrier-grade voice services
- Dual-band concurrent Wi-Fi: 2.4GHz and 5GHz
- Wireless IEEE 802.11 b/g/n/ax: 2.4GHz
- Wireless IEEE 802.11ac/ax: 5GHz
- Network Address Translation (NAT) and firewall
- Voice interworking function from the analog POTS lines to the voice over IP (VoIP) and Ethernet layers
- One USB 3.0 host port
- Optics support received signal strength indication (RSSI)
- Supports virtual private network (VPN) passthrough for Point-to-Point Tunneling Protocol (PPTP), Layer 2 Tunneling Protocol (L2TP) and IPSec
- Port forwarding and demilitarized zone (DMZ)/dynamic domain name system (DDNS)

## Benefits

- Integrates the ONT and wireless access point functions to allow for one less device in the home
- Delivers connectivity to Ethernet devices within the home
- Comes equipped with Nokia WiFi Mesh Middleware
- Supports full triple play services, including voice, video and data
- Allows service-per-port configurations

- Supports IP video distribution
- Supports easy-to-use USB 3.0 connections for external disk drives and home network attached storage (NAS)
- Delivers voice services using VoIP
- Delivers video services efficiently with multicasting or unicasting
- Facilitates network management using Nokia 5520 AMS
- Flexible video delivery options of Ethernet or wireless to set-top boxes (STBs)

## Technical specifications

### Physical

- Height: 195 mm (7.7 in)
- Width: 245 mm (9,65 in)
- Depth: 37 mm (1.46 in)
- Weight: 650g (1.4lb)

### Installation

- Desk mountable
- Wall mountable with bracket

### Operating environment

- Temperature: -5°C to 45°C (23°F to 113°F)
- Relative humidity: 10% to 90%

### Power requirements

- Local powering with 12 V input (feed uses external AC/DC adapter)
- Dying gasp support
- Power consumption: <36 W

### XGS PON uplinks

- Wavelength: 1260 nm–1280 nm upstream; 1575 nm–1580 nm downstream
- G.9807.1 XGS PON standards compliant: 4 dBm ~ 9 dBm launch power; -28 dBm ~ -9 dBm for receiving
- SC/APC connector

- 10 G burst mode upstream transmitter
- 10 G downstream receiver
- G.9807.1-compliant 10 GPON Encapsulation Method (XGEM) framing
- Flexible mapping between XGEM ports and T-CONT
- Advanced Encryption Standard (AES) 128
- Forward error correction (FEC)
- Activation with automatic discovered serial number and password
- Remote software image download
- BOSA On Board (BOB) type laser, SC/APC connector

## Ethernet interfaces

- 10/100/1000Base-T interface with RJ-45 connectors
- Wi-Fi Protected Access (WPA) support, including pre-shared key (WPA-PSK), WPA2, WPA3
- Forwarding
- Ethernet port auto-negotiation or manual configuration with medium dependent interface /medium dependent interface crossover (MDI/MDIX)
- Virtual switch based on IEEE 802.1q virtual LAN (VLAN)
- VLAN tagging/de-tagging per Ethernet port and marking/remarking of IEEE 802.1p
- IP type of service/differentiated services code point (ToS/DSCP) to IEEE 802.1p mapping for untagged frames
- Class of service (CoS) based on VLAN ID, IEEE 802.1p bit
- Internet Group Management Protocol (IGMP) v2/ v3 snooping

## POTS interfaces

- Two FXS ports for VoIP service with RJ-11 connectors
- Multiple codecs: ITU-T G.711, ITU-T G.729
- SIP (RFC 3261)
- ITU-T G.168 echo cancellation
- Services: caller ID, call waiting, call hold, 3-way call, call transfer, message waiting indication
- 5 ringer equivalence numbers (RENs) per line
- Dual-tone multi-frequency (DTMF) dialing
- Balanced sinusoidal ring signal, 55 V root mean square (RMS)

## WLAN interfaces

- 2x2 MIMO on 802.11b/g/n/ax
- 2x2 MIMO on 802.11a/n/ac/ax
- 3 dBi internal antenna
- WPA, WPA-PSK/TKIP, WPA2, WPA2-PSK/AES, WPA3
- Media access control (MAC) filters

## USB interface

- One USB 3.0 interfaces

## Residential gateways

- IPv4 and IPv6
- Point-to-Point Protocol over Ethernet (PPPoE) and IP over Ethernet (IPoE)
- NAT, DMZ and firewall
- Dynamic Host Configuration Protocol (DHCP) and domain name system (DNS) proxy
- IGMP proxy
- Supports TR-069



## LEDs

- Power
- Link
- Auth
- LAN (1~4)
- TEL (1~2)
- VoIP
- Wi-Fi Protected Setup (WPS)

- WLAN 2.4G/5G
- USB
- Internet

## Safety and electromagnetic interference (EMI)

- Protection of over voltage/current

## Regulatory compliances

- CE Mark
- FCC Mark

## About Nokia

We create the technology to connect the world. Only Nokia offers a comprehensive portfolio of network equipment, software, services and licensing opportunities across the globe. With our commitment to innovation, driven by the award-winning Nokia Bell Labs, we are a leader in the development and deployment of 5G networks.

Our communications service provider customers support more than 6.4 billion subscriptions with our radio networks, and our enterprise customers have deployed over 1,300 industrial networks worldwide. Adhering to the highest ethical standards, we transform how people live, work and communicate. For our latest updates, please visit us online [www.nokia.com](http://www.nokia.com) and follow us on Twitter [@nokia](https://twitter.com/nokia).

Nokia operates a policy of ongoing development and has made all reasonable efforts to ensure that the content of this document is adequate and free of material errors and omissions. Nokia assumes no responsibility for any inaccuracies in this document and reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

Nokia is a registered trademark of Nokia Corporation. Other product and company names mentioned herein may be trademarks or trade names of their respective owners.

© 2020 Nokia  
Nokia Oyj  
Karakaari 7  
02610 Espoo  
Finland  
Tel. +358 (0) 10 44 88 000

Document code: (October) CID210105